



Life Sciences



VHP® LTS-V

Low Temperature Sterilizer






The only and original patented industrial scale VHP sterilizer product line for low temperature surface sterilization in Pharmaceutical and Medical Device manufacturing facilities. The largest and growing install base of sterilizer equipment with FDA-approved terminal sterilization processes applied.

The VHP® LTS-V Low Temperature Sterilizer is an advanced GMP terminal surfaces sterilization system utilizing Vaporized Hydrogen Peroxide. The LTS-V technology provides biopharmaceutical manufacturers and CMO's an in-house solution for sterilizing the packaging, containers and surfaces of temperature or radiation sensitive drug pre-filled syringes, vials, implants, electronics, and various other sensitive medical devices. The sterilization process is designed to achieve SAL 10^{-6} for exposed device and packaging surfaces intended to be sterilized. The sterilization process is validated per ISO 14937.

STERIS' cycle recipes are developed to meet specific customer product and throughput requirements. The VHP LTS-V Sterilizer incorporates patented VHP dry vapor technology, renowned throughout the industry for its superior efficacy, material compatibility and safety.

Product Applications

- Heat / radiation sensitive injectable drugs in pre-filled syringes (e.g., ophthalmic)
- Hip, knee and skull implants – any implants with sensitive materials and residual concerns
- Implants with electronics (e.g., pacemakers, seizure preventers)
- Subcutaneous applications for monitoring or drug delivery



Advantages

- In-house solution for sterilization of sensitive product loads
- Increased throughput
- Savings in manual labor
- Savings in facility cost
- Proven VHP technology with excellent material compatibility and compliance
- Comprehensive STERIS expert services from feasibility testing to validation and global field services

Unit Size Chamber Volume

VHP® LTS-V 6912	850 liters
VHP® LTS-V 91515	2000 liters
VHP® LTS-V 151818	4000 liters
VHP® LTS-V 182124	9000 liters

Features and Configurations

- cGMP and cGAMP compliant design
- Single or double-door configuration
- 2...4 -hour cycles typical
- Processing temperature range +28...40 °C, max. temperature +50 °C
- Unique patented VHP vaporization and chamber distribution process utilizing a chamber fan and relative humidity (RH%) PID-control
- Utilizes VAPROX® hydrogen peroxide*
- Low peroxide consumption, low residual levels
- Utility requirements include only RO/DI -water, softened water, instrument air and 3-phase electricity
- Electronic Data Security enabling 21 CFR Part 11 and Annex 11 compliance as standard
- Stainless steel chamber and loading systems
- Standardized loading carts and trolleys design with flexibility for different products and loading configurations

*Vaprox is a registered trademark for STERIS Corporation



STERIS Expert Services



■ By STERIS ■ By Customer

Comprehensive STERIS Services

- STERIS global application experts provide our Customers comprehensive feasibility, cycle development and process validation services per ISO 14837
- STERIS global services reach our Customers worldwide
- STERIS technical specialists provide full installation supervision, start-up calibration and IQ/OQ services and Site Acceptance Testing (SAT) services to guarantee a professional migration into the Customer's environment
- STERIS services provide comprehensive training and Preventative Maintenance Plans

